

Data Sheet

Fujitsu PRIMERGY SX960 S1 Storage Blade Disk

Simple and low-priced direct-attached and shared-storage solution for PRIMERGY BX Blade Servers

PRIMERGY SX storage blades are installed together with PRIMERGY server blades in the PRIMERGY BX chassis. The introduction of storage blades is a simple and low-priced way to consolidate servers. Above all, small and medium-sized companies usually have rack and tower servers which offer a high degree of capacity regarding local hard disks. The use of storage blades equipped with tape drives is a simple and quick method to backup system data locally. Having local access to large amounts of data is often necessary, for example, in the world of computer-aided engineering (CAE), where smaller local workgroups have to access and create very large models. Examples for using storage blades are operation within limited environments as a file server or for Microsoft® SharePoint portals.

PRIMERGY SX960 S1

The Fujitsu PRIMERGY SX960 Storage Blade offers direct-attached storage for the PRIMERGY BX Blade Server with support of up to 10 hot-plug SAS or SATA hard disks. The storage blade can be inserted, like a server blade, in the front of the blade server housing. It can be hot-plugged and used with various types of server blades. The BX Blade Servers' midplanes offer PCI Express connections to the adjacent server blades, enabling top-quality memory access without using additional cables. The PRIMERGY SX960 Storage Blade has an onboard LSI MegaRAID controller with 512 MB Write Back Cache and optional Battery Backup Unit, for top performance and data security.

Within PRIMERGY BX system units you can use NetApp Data ONTAP-v™ software to convert the PRIMERGY SX960 Storage Blade into a SAN within the PRIMERGY BX housing. The so-called

PRIMERGY VSX960 is a flexible solution which provides a shared-storage device for all other server blades in the blade enclosure. This virtual storage solution consists of a storage control blade with an installed Hypervisor plus the Data ONTAP-v™ software from NetApp and a PRIMERGY SX960 Storage Blade which provides the shared storage capacity. The PRIMERGY VSX960 is completely integrated in the ServerView Appliance and supports up to 10 SAS hard disk drives in a RAID array. The ServerView Installation Manager ensures a simple installation option directly on the customer premises. The VSX960 storage solution supports iSCSI, CIFS and NFS protocols and supports Data ONTAP-v™ functions, such as Snapshot, FlexVol, SnapRestore, SnapVault and FilerView.



Features and Benefits

Main Features	Benefits
<p>Operational diversity</p> <ul style="list-style-type: none"> PRIMERGY SX960 S1 supports up to 10 hot-plug SAS or SATA hard disks with a half-height and double-wide form factor. 	<ul style="list-style-type: none"> High capacity with up to 10 TB SATA HDDs, 9 TB with top-quality 2.5-inch SAS drives and up to 640 GB with power-saving 2.5-inch SATA SSDs. The Virtual Storage Appliance (VSA) offers an optimal, easy-to-handle datacenter-in-the-box solution which is ideally suitable for medium-sized customers. Avoidance of additional cabling due to the direct connection to Server Blade(s) via the high performance midplane, no need for additional disk controller slots in Server Blade(s). The write-back cache comprehensively enhances the speed of write operations and in the event of power failures, the optional Battery Backup Unit guarantees highest data integrity.
<p>Shared storage</p> <ul style="list-style-type: none"> PRIMERGY VSX960 uses NetApp Data ONTAP-v™ software in order to convert the PRIMERGY SX960 storage blade into a SAN within the PRIMERGY BX system units. A flexible solution providing shared-storage capacity for all other server blades in the blade server housing. 	
<p>Fast interconnect</p> <ul style="list-style-type: none"> Midplane connection via PCIe x4 interface 	
<p>Enhanced speed plus secure data transmission</p> <ul style="list-style-type: none"> High-performance RAID controller within the storage blade, secured for RAID levels 0, 1, 5 and 6, with 512 MB cache module with ECC and with optional BBU. 	

Technical details

Enclosure

Type	Storage extension unit for BX92x and BX96x Server Blades
Number of hard disk drives	1 - 10
Storage architecture	Direct Attached Storage (DAS)
Status LEDs	Power (green) Identification (blue)

Storage disks

SSD SATA, 3 Gb/s, 64 GB, SLC, hot-plug, 2.5-inch, enterprise
SSD SATA, 3 Gb/s, 32 GB, SLC, hot-plug, 2.5-inch, enterprise
HDD SATA, 3 Gb/s, 500 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 3 Gb/s, 320 GB, 5400 rpm, hot-plug, 2.5-inch, economic
HDD SATA, 3 Gb/s, 250 GB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SATA, 3 Gb/s, 160 GB, 5400 rpm, hot-plug, 2.5-inch, economic
HDD SATA, 3 Gb/s, 1 TB, 7200 rpm, hot-plug, 2.5-inch, business critical
HDD SAS, 6 Gb/s, 900 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 600 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 450 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 6 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 3 Gb/s, 300 GB, 10000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 3 Gb/s, 146 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise
HDD SAS, 3 Gb/s, 73 GB, 15000 rpm, hot-plug, 2.5-inch, enterprise

RAID Controller

Integrated RAID 5/6 Ctrl., HDD SAS 6 Gb, Fujitsu , 8 ports int. RAID level: 0, 1, 10, 5, 50, 6, 60, 512 MB Cache, Optional BBU (based on LSI SAS2108)
--

Dimensions / Weight

Dimensions (W x D x H)	90 x 508 x 204 (chassis height 210,5) mm
Weight	max. 8 kg (fully equipped)
Weight notes	Actual weight may vary depending on configuration

Environmental

Temperature note	In accordance with the corresponding PRIMERGY BX400 and BX900 system unit
Operating environment	FTS 04230 Guideline for Data Center (installation locations)
Operating environment Link	http://docs.ts.fujitsu.com/dl.aspx?id=d4ebd846-aa0c-478b-8f58-4cfbf3230473

Power supply configuration

Active power (min. configuration)	70 W
Active power (max. configuration)	110 W
Heat emission	396.0 kJ/h (375.3 BTU/h)

Compliance

Germany	GS
Europe	CE Class A *
USA/Canada	CSA us CSA c
Global	CB RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment)
Japan	VCCI
Taiwan	BSMI

Compliance

Compliance notes

In combination with corresponding PRIMERGY BX system unit
There is general compliance with the safety requirements of all European countries and North America. National approvals required in order to satisfy statutory regulations or for other reasons can be applied for on request.
* Warning:
This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Compliance link

<http://sp.ts.fujitsu.com/sites/certificates/>

More information

Fujitsu platform solutions

In addition to Fujitsu PRIMERGY SX960 S1, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Dynamic Infrastructures

With the Fujitsu Dynamic Infrastructures approach, Fujitsu offers a full portfolio of IT products, solutions and services, ranging from clients to datacenter solutions, Managed Infrastructure and Infrastructure as-a-Service. How much you benefit from Fujitsu technologies and services depends on the level of cooperation you choose. This takes IT flexibility and efficiency to the next level.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRIMERGY SX960 S1, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
<http://www.fujitsu.com/PRIMERGY>

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to resolve issues of environmental energy efficiency through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner

Contact

FUJITSU LIMITED

Website: www.fujitsu.com
2012-01-24 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>
Copyright © Fujitsu Technology Solutions